

08-1-00

A

NEW, CONTINUATION, DIVISIONAL OR
CONTINUATION-IN-PART APPLICATION
UNDER 37 C.F.R. §1.53(b)

Attorney Docket No. 9432-000116

Express Mail Label No. EL 581 391 665 US

Date July 31, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Hon. Commissioner of Patents and Trademarks
Washington, D. C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. §1.53(b) is a patent application for RECOGNITION SYSTEM USING LEXICAL TREES

identified by: ☐ First named inventor,
or ☒ Attorney Docket No. (see above)

Type of Application

☒ This application is a new (non-continuing) application.

☐ This application is a ☐ continuation / ☐ divisional / ☐ continuation-in-part of prior application No. _____. Amend the specification by inserting before the first line the sentence:

--This is a [continuation/division/continuation-in-part] of United States patent application No. _____, filed _____.--

☐ The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

If for some reason applicant has not requested a sufficient extension of time in the parent application, and/or has not paid a sufficient fee for any necessary response in the parent application and/or for the extension of time necessary to prevent the abandonment of the parent application prior to the filing of this application, please consider this as a Request for an Extension for the required time period and/or authorization to charge our Deposit Account No. 08-0750 for any fee that may be due. THIS FORM IS BEING FILED IN TRIPLICATE: one copy for this application; one copy for use in connection with the Deposit Account (if applicable); and one copy for the above-mentioned parent application (if any extension of time is necessary).

2. Contents of Application

a. Specification of 32 pages;

- ☐ A microfiche computer program (Appendix);
☐ A nucleotide and/or amino acid sequence submission;

☐ Because the enclosed application is in a non-English language, a verified English translation ☐ is enclosed ☐ will be filed.

☐ Cancel original claims _____ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing date purposes.)

b. ☒ Drawings on 7 sheets;

07/31/00

Jc542 U.S. PTO

Jc542 U.S. PTO

09/628828

07/31/00

Jc542 U.S. PTO

- c. ☒ A signed Oath/Declaration ☒ is enclosed / ☐ will be filed in accordance with 37 C.F.R. §1.53(f).

The enclosed Oath/Declaration is ☒ newly executed / ☐ a copy from a prior application under 37 C.F.R. §1.63(d) / ☐ accompanied by a statement requesting the deletion of person(s) not inventors in the continuing application.

d. **Fees**

FILING FEE	Number	Number	Basic Fee
CALCULATION	Filed	Extra	Rate
Total Claims	20 - 20 =	0 x	\$18.00 = 0.00
Independent Claims	2 - 3 =	0 x	\$78.00 = 0.00
Multiple Dependent Claim(s) Used			\$260.00 =
FILING FEE - NON-SMALL ENTITY			690.00
FILING FEE - SMALL ENTITY: Reduction by 1/2			
<input type="checkbox"/> Verified Statement under 37 C.F.R. §1.27 is enclosed.			
<input type="checkbox"/> Verified Statement filed in prior application.			
Assignment Recordal Fee (\$40.00)			
37 C.F.R. §1.17(k) Fee (non-English application)			
TOTAL			690.00

- ☒ A check is enclosed to cover the calculated fees. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to Deposit Account No. 08-0750. A duplicate copy of this document is enclosed.
- ☐ The calculated fees will be paid within the time allotted for completion of the filing requirements.
- ☐ The calculated fees are to be charged to Deposit Account No. 08-0750. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to said Deposit Account. A duplicate copy of this document is enclosed.

3. **Priority Information**

- ☐ **Foreign Priority:** Priority based on _____ Application No. _____, filed _____, is claimed.
- ☐ A copy of the above referenced priority document ☐ is enclosed / ☐ will be filed in due course, pursuant to 35 U.S.C. §119(a)-(d).
- ☐ **Provisional Application Priority:** Priority based on United States Provisional Application No. _____, filed _____, is claimed under 35 U.S.C. §119(e).

Attorney Docket No. 9432-000116

Express Mail Label No. EL 581 391 665 US

Date July 31, 2000


4. Other Submissions

- ☐ A Preliminary Amendment is enclosed.
- ☐ An Information Disclosure Statement, _____ sheets of PTO Form 1449, and _____ patent(s)/publications/documents are enclosed.
- ☒ A power of attorney
- ☒ is submitted ☒ with the new Oath/Declaration.
- ☐ is of record in the prior application and ☐ is in the original papers / ☐ a copy is enclosed.
- ☐ An Assignment of the invention
- ☐ is enclosed with a cover sheet pursuant to 37 C.F.R. §§3.11, 3.28 and 3.31.
- ☐ is of record in a prior application. The assignment is to _____, and is recorded at Reel _____, Frame(s) _____.
- ☐ An Establishment of Assignee's Right To Prosecute Application Under 37 C.F.R. §3.73(b), and Power Of Attorney is enclosed.
- ☒ An Express Mailing Certificate is enclosed.
- ☐ Other: _____

Attention is directed to the fact that the correspondence address for this application is:

Harness, Dickey & Pierce, P.L.C.
P.O. Box 828
Bloomfield Hills, Michigan 48303
(248) 641-1600.

Respectfully,



Gregory A. Stobbs, Reg. No. 28,764

Date July 31, 2000

Harness, Dickey & Pierce, P.L.C.
P.O. Box 828
Bloomfield Hills, Michigan 48303
(248) 641-1600

HARNES, DICKEY & PIERCE, P.L.C.
ATTORNEYS AND COUNSELORS
P.O. BOX 828
BLOOMFIELD HILLS, MICHIGAN 48303
U.S.A.

TELEPHONE
(248) 641-1600
TELEFAX/IMILE
(248) 641-0270

Date July 31, 2000

Hon. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Sir:

EXPRESS MAILING CERTIFICATE

Applicant: Luca Rigazio et al.

Serial No (if any):

For: RECOGNITION SYSTEM USING LEXICAL TREES

Docket: 9432-000116

Attorney: Gregory A. Stobbs

"Express Mail" Mailing Label Number EL 581 391 665 US

Date of Deposit July 31, 2000

I hereby certify and verify that the accompanying Check in the amount of \$690.00, Transmittal Letter Under 37 C.F.R. § 1.53(b) (in duplicate), 32 Page Patent Application including 20 claims, and an Abstract, Signed Declaration and Power of Attorney, 7 Pages of Informal Drawings (Showing Figures 1-3, 4a-b, 5 and 6) and Return Postcard (is) are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" service under 37 C.F.R. 1.10 on the date indicated above and (is) are addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.



Signature of Person Mailing Document(s)

RECOGNITION SYSTEM USING LEXICAL TREES

BACKGROUND AND SUMMARY OF THE INVENTION

The present invention relates generally to speech recognition systems. More particularly, the invention relates to dynamic programming pattern sequence recognition techniques in isolated word and continuous speech recognition applications.

Dynamic programming techniques are commonly used today for time-warping problems in both isolated and continuous speech recognition and optimum word sequence searching problems in continuous speech (connected word) recognition. A well known type of dynamic programming recognition that can be used in the context of the Hidden Markov Model (HMM) is the Viterbi algorithm. Dynamic programming techniques can also be used with a variety of other types of speech models besides HMMs, such as neural network models, for example.

The classic Viterbi algorithm is an inductive algorithm in which at each instant (each frame) the algorithm stores the best possible state sequence for each of the n states as an intermediate state for the desired observation sequence O . In this way, the algorithm ultimately discovers the best path for each of the n states as the last state for the desired observation sequence. Out of these, the algorithm selects the one with the highest probability. The classic Viterbi algorithm proceeds frame, by

frame, seeking to find the best match between a spoken utterance and the previously trained models.

Taking the case of a Hidden Markov Model recognizer as an example, the probability of the observed sequence (the test speaker's utterance) being generated by the model (HMM) is the sum of the probabilities for each possible path through all possible observable sequences. The probability of each path is calculated and the most likely one identified. The Viterbi algorithm calculates the most likely path and remembers the states through which it passes.

The classic Viterbi algorithm is computationally expensive. It keeps extensive linked lists or hash tables to maintain the list of all active hypotheses, or tokens. A great deal of computational energy is expended in the bookkeeping operations of storing and consulting items from these lists or tables.

Because the classic Viterbi algorithm is computationally expensive, it can noticeably slow down the apparent speed of the speech recognizer. This is especially problematic in real-time systems where a prompt response time is needed. The current solution is simply to use more powerful processors—an expensive solution which can be undesirable in some embedded systems and small consumer products, like cellular telephones and home entertainment equipment.

The present invention seeks to improve upon the classical Viterbi algorithm and is thus useful in applications where processing power is limited. In our experiments we have shown that our new technique improves recognition speed by at least a factor of three. The invention
5 employs a unique lexical tree structure with associated searching algorithms that greatly improve performance. While the system is well-suited for embedded applications and consumer products, it can also be deployed in large, high-speed systems for even greater performance improvement. The algorithm can be used for isolated word recognition, or
10 as a first pass fast match for continuous speech recognition. It can also be extended to cross-word modeling.

For a more complete understanding of the invention, its objects and advantages, refer to the following specification and to the accompanying drawings.

15

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram of a speech recognizer illustrating how a decoder constructed in accordance with the present invention may be used to implement a model-based recognizer;

20

Figure 2 shows the presently preferred data structure for the lexical tree employed by the invention;

Figure 3 is a data structure diagram used to represent each node of the lexical tree;

Figure 4a is a timeline diagram illustrating the basic task performed by a decoder employing the invention in a continuous speech application;

Figure 4b is a tree diagram, showing how the active envelope is traversed;

Figure 5 is a series of tree diagrams useful in understanding the dynamic behavior of the algorithm;

Figure 6 is a flowchart of the algorithm.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Background

Figure 1 illustrates an exemplary speech recognition system. The system operates in two phases: a training phase, during which the system learns the reference patterns representing the different speech sounds (e.g., phrases, words, phones) that constitute the vocabulary of the application; and a recognition phase, during which an unknown input pattern is identified by considering the set of references. During the training phase each reference is learned from spoken examples and stored either in the form of templates obtained by some averaging method (in template-matching systems) or models that characterize the statistical properties of patterns (like in stochastic systems). One of the most

popular stochastic systems utilizes a statistical modeling approach employing Hidden Markov Models (HMM).

As illustrated in Figure 1, the exemplary speech recognizer performs the recognition process in three steps. As depicted at **10**,
5 speech analysis and feature extraction is first performed on the input speech. This step focuses on extracting a set of parameters obtained by signal analysis. The next step, depicted at **12**, involves pattern classification. It is at this step that the classic Viterbi algorithm would be performed. During this step a similarity measure is computed between the
10 input speech and each reference pattern. The process defines a local measure of closeness between feature vectors and further involves a method for aligning two speech patterns, which may differ in duration and rate of speaking. The pattern classification step uses a template or model dictionary **14** containing the information generated during the training
15 phase. The final step is the decision step **16**. During this step the unknown pattern is assigned the label of the "closest" reference pattern. Typically, this decision is based on rules which take into account the results of the similarity measurements.

Because many recognizers in popular use today employ Hidden
20 Markov Models as a model of speech, a simple illustration of a Hidden Markov Model is shown at **20** in Figure 1. It will be recognized, however, that the principles of the present invention are not limited to recognizers

employing Hidden Markov Models. A three-state Hidden Markov Model is illustrated in Figure 1, with the states designated s_1 , s_2 and s_3 . Of course, a working implementation could employ a different number of states, and the number of states selected here is merely for illustration purposes. Although the invention is not restricted to LR (left-to-right) HMMs, the algorithm provides best results with this class of models. Hence the HMM illustrated in Fig. 1 is an LR HMM in which state transitions proceed only from left to right, without jumping states.

The Hidden Markov Model involves a collection of probabilities, some associated with the states themselves and others associated with the making a transition from that state to another state or to itself. In Figure 1, state transitions are illustrated by arrows. Note that some arrows depict a transition from one state to a different state, whereas other arrows depict a transition from one state to itself.

Each phrase, word or phone to be represented by the speech models will have its own model, consisting of probability values associated with each transition and associated with each state. Thus each self-loop has an associated transition probability, depicted at **22**; each loop to another state has its associated transition probability **24**. In addition, each state has probability information associated with it, as well.

Because the probability values associated with each state may be more complex than a single value could represent, some systems will

represent the probabilities associated with each state in terms of a Gaussian distribution. Sometimes, a mixture of multiple distributions are used in a blended manner to comprise Gaussian mixture density data. Such data are shown diagrammatically at **26** and referenced by a mixture index pointer **28**. Thus associated with each state is a mixture index pointer, which in turn identifies the Gaussian mixture density information for that state. It, of course, bears repeating that the speech recognizer and Hidden Markov Model structure illustrated in Figure 1 are intended to be merely exemplary of one type of recognizer with which the invention may be used. In general, the invention may be used with any system that performs dynamic programming in pattern classification. As previously noted, best HMM results are obtained with a LR HMMs. Thus the invention may be employed, for example, in place of the classical Viterbi algorithm.

For more information regarding the basic structure of speech recognition systems and of Hidden Markov Modeling, see Junqua, Jean-Claude and Haton, Jean-Paul, *Robustness in Automatic Speech Recognition, Fundamentals and Applications*, Kluwer Academic Publishers, 1996.

The Preferred Data Structure

The present invention may be used to greatly improve the way in which the pattern classification step **12** is performed. The invention

employs a unique data structure for representing the template or model dictionary **14**, in combination with a unique algorithm that traverses the data structure to discover the best matching hypothesis. The preferred data structure will be described in this section; the preferred algorithm will be described in the next section. The preferred data structure represents the template or model dictionary **14** as a lexical tree that has been flattened to a linked list. Figure 2 illustrates this topology. Figure 2, more specifically, shows an example of a lexical tree **30** that stores individual words that are made up of letters. The algorithm, described later below, traverses this lexical tree in a time-synchronous fashion and applies dynamic programming equations at each active node. The algorithm thus traverses the tree, from node to node, testing whether or not the letter at each node matches the letter identified in the feature extraction step **10** (Fig. 1).

In considering the exemplary lexical tree presented in Fig 2, it should be recognized that the illustrated example, which uses words made up of the letters that spell those words, is merely selected here for teaching purposes. In a speech recognition system the features extracted during speech analysis at step **10** might be features or their corresponding sound units such as phonemes, syllables or the like. In other words, the invention is not limited to only applications in which individual letters are tested at each node to identify the word that those

letters spell. Rather, any suitable unit may be used at each node. In a continuous speech recognizer, for example, the system might represent entire words at each node, and the lexical trees would contain pointers to entire phrases or sentences made up of those words.

5 Referring to Figure 2, note that the lexical tree **30** is represented as a flattened linked list **32** that includes a number of specific features to identify, not only the topology of the list, but also the route that the list would be traversed to mirror a traversal of the corresponding tree. More specifically, the list is constructed so that all nodes at the same descent
10 level within the tree are represented as contiguous entries in the list. Thus the linked list begins with a first structure or node to represent the root node of the tree. Beneath the root node structure are the structures for the next immediate child nodes, corresponding in this example to nodes k and h of the tree. Proceeding with the linked list, the next two nodes in
15 this example represent the second tier children, namely nodes aa and aa of the tree. The next three nodes represent the third tier grandchildren, nodes r, r and l. Finally, the last four nodes represent the last tier of the tree, namely nodes d, d, t and t.

 The nodes within the linked list store more than just the letter or
20 sound unit that corresponds to each node in the tree. Each node also includes at least one forward pointer to the next node that would be traversed if one were traversing the tree. Thus the first child node k

includes a pointer to the grandchild node aa, to illustrate how one would traverse the tree from node k to node aa in ultimately spelling the sound units corresponding to the word CARD. The structure of each node also includes a flag, represented in Figure 2 as a small box in the lower right-hand corner. This flag is set to identify if that node represents the last child of its parent. This information is used to further describe the topology of the tree as it is expressed in the flattened linked list form.

The actual representation of the linked list takes the form of a data structure shown in Figure 3. The structure of Figure 3 illustrates how the flattened linked list nodes might be configured for a recognizer that uses Hidden Markov Models. The nodes may be readily configured to store other types of parameters, as well. Thus the illustration of Figure 3 should not be understood as a limitation upon the scope of the invention. The structures can be used to store parameters and/or template information corresponding to recognizers other than Hidden Markov Model recognizers.

Referring to Figure 3, each node stores the topological structure of the tree as follows. It includes a data element 50 in which is stored the pointer from that node to its next child node. These pointers correspond to those illustrated in Figure 2 and are used when traversing the tree. The node data structure also includes a Boolean flag 52 that is either set or not set to indicate whether that node is the last child of its parent. This

information was illustrated diagrammatically in Figure 2 by the small boxes that are either unfilled (FALSE) or filled (TRUE).

Because the illustrated example is designed to represent Hidden Markov Models, the node data structure includes data elements **54** that
5 contain the transition probabilities associated with the self-loop and loop to child probabilities associated with that node. In a typical recognizer these would be floating point values corresponding to the probabilities illustrated in Figure 1 at **22** and **24**. The node data structure also includes a data element **56** in which an index or pointer is stored to identify the
10 corresponding Gaussian mixture densities of that node. The mixture index pointer was shown at **28** in Figure 1. In turn, it points to a collection of data representing the Gaussian mixture density **26** or other probability values used by the recognizer to represent the probability that a given node would emit a given sound unit.

15 The remaining data elements in the node data structure are used by the algorithm that determines which traversal represents the best path or best match. Data element **58** stores the cumulative probability score associated with that node as the algorithm performs its analysis process. Data element **60** stores a pointer to another node within the tree, known
20 as the next active node. The algorithm uses the next active node to determine how it will proceed through the tree. The details of the

algorithm and how these data elements come into play will be described next.

The Algorithm

The preferred algorithm traverses the data structure, described above, in a time-synchronous fashion. That is, the algorithm traverses the nodes in synchronism with the observation data developed as the feature extraction process (step 10 in Fig. 1) proceeds. In a typical recognizer, the input speech is temporally segmented or subdivided into frames. The preferred algorithm thus operates in synchronism with these frames.

Traversal from node to node is dictated by the topological structure of the tree and also by a second structure called the *active node envelope*. Active nodes are those node that currently represent the most likely match hypotheses. The active node envelope is a linked list of these currently active nodes. The active node envelope represents a dynamic structure. Nodes will join or leave the active node list as the algorithm proceeds. Nodes are added to the active list if their probability score is above a beam search threshold and formerly active nodes are cut from the active list if their score falls below that threshold. To compute the probability score of an active node, the algorithm applies the following dynamic programming equation to each active node:

$$s_k(t) = \max \{s_\phi(t-1) + a_{\phi,k}\} + d_k(t)$$

where $s_k(t)$ is the score at time t , and ϕ is the node's parent.

To understand how the algorithm traverses the lexical tree, a few definitions should be made. With reference to the lexical tree, we define the *depth* of the node as the number of states on that node's left. See Figure 4a. The greater the number, the deeper the node. We define a *column* of the lexical tree as the set of nodes of the same depth. For each column we define an arbitrary order relation on the nodes. The *active envelope* or *active node list* is the list of nodes that are active, ordered given a relation such that, if node n is a node with parent n^* , and node k is a node with parent k^* , $k^* < n^*$ implies $k < n$. Since all nodes of a given depth in the lexical tree can be processed in almost any arbitrary order, we chose the traversing sequence that maximizes the performance of the memory cache. In other words, when the processor loads a given address from memory, it's onboard cache mechanism will also load a block of contiguous addresses that immediately follow the address being loaded from memory. Thereafter, if any of those subsequent addresses need to be accessed, the processor will access them from its cache, instead of from memory, thereby eliminating the associated memory access time. The present invention traverses the lexical tree so that it exploits this feature of the cache. The lexical tree is encoded so that the algorithm will traverse the tree in a direction that utilizes the information stored in the cache.

To further illustrate, let the nodes of Fig. 2 be ordered in a contiguous array in memory. The preferred embodiment will thus traverse the nodes in increasing order of the memory heap. The preferred traversal path is illustrated in Figure 4b. Traversal starts at the active node of greatest depth and then proceeds in increasing order within a given column. Once all active nodes within a column have been traversed, the path proceeds to the previous column.

The presently preferred algorithm proceeds through the following steps:

- 10 1. Start from the deepest active list in the lexical tree.
2. Let B be the smallest ranked node in the active list of the children column.
3. Traverse the active list in increasing order.
4. For each child c of the current node k,
- 15 5. If $B < c$, then increment B until that condition is false.
6. If $B = c$, then apply the dynamic programming equation.
7. If $B > c$, then simply link c before n.
8. Decrement the depth and process the parent column.

The above algorithm compares the sequential output of the speech analysis module with the entries in its lexical tree, at each node determining which entry has the highest probability of matching the input speech utterance. While it is possible to exhaustively analyze each node

of the tree, this brute force approach is very time-consuming and inefficient. The preferred algorithm dynamically reduces its search space at each successive iteration by identifying the nodes that currently have the highest probability of matching the input utterance. The algorithm
5 identifies these nodes as the next active nodes. It uses these nodes, and only these nodes, in its subsequent iteration.

As the algorithm visits each node, it computes the probability score of that node. If we define the loop and incoming probabilities as $l_k = a_{k,k}$ and $i_k = a_{k^*,k}$. The score $s_k(\cdot)$ at time $t+1$ can be computed as:
10
$$s_k(t+1) = \max\{s_k(t) + l_k, s_k(t) + i_k\} + d_k(t).$$

Note that the algorithm uses t and $t+1$ instead of t and $t-1$ to denote a *forward* recursion instead of a *backwards* recursion. The ultimate goal is to compute a score based on knowledge of child notes only (i.e., from k^* and not from k) to avoid use of back-pointers (i.e.,
15 knowledge of the parent node).

The algorithm defines the *topological score* $r_k(t) = s_k(t) - d_k(t)$ and the *partial topological score* $r^{\wedge}(t) = s_k(t) + l$. Note that the partial topological score equals the topological score when k^* does not belong to an active list. The algorithm traverses a cell in the active envelope by
20 performing the following operations:

1. Compute score $s_k \leftarrow r_k + d_k$ (acoustic match);

2. Bequeathal: for each child c , $r_c \leftarrow \max\{s_k + i_c, r_c\}$. The score field of the child is assumed to hold the partial score r^* .

3. Self-activation: $r_k \leftarrow r_k^* + i_k$. The score field now holds the partial topological score. If no score inheritance takes place then this is also the topological score for $t+1$.

As indicated by the above steps, each cell k computes its own topological score and acoustic scores at each frame. We call this property *self-activation*. Each cell activates itself and then all of its children. If the children have already activated themselves, the parent cell's score is bequeathed to its children. Bequeathal and self-activation can be inverted if the algorithm keeps s_k and the next active node in variables. In such case data from a node can be discarded from the memory cache immediately after self-activation. Note that during the bequeathal process a node has direct access to its children. This is ensured by the way the active envelope is constructed, as described above.

Dynamic Behavior of Algorithm and Active Node Envelope Propagation

As noted above, the active node envelope is a dynamic structure. The active nodes change as the algorithm proceeds. When the active node envelope is superimposed onto the lexical tree, the active node envelope will appear to propagate as the algorithm operates over time. This concept is shown diagrammatically in Figure 4a.

Figure 4a shows an example where words, instead of letters, are represented at each node. In the preceding examples, an individual word recognizer was illustrated. Each node of the tree represented a letter or sound unit that comprises a word in the dictionary. However, it will be recalled that the techniques of the invention can be used in both individual word and continuous speech recognizers. Thus Figure 4a shows how the tree structure might look in a continuous speech recognizer, in which individual words are represented at each node and the output would be sentences or phrases. By examining the tree 70 in Figure 4a one can see, for example, how the phrase "the quick brown fox" would be constructed by appropriate traversal of the tree.

Figure 4a shows how the active node envelope will appear to propagate over time. Timeline 72 shows how the next active node envelope for the exemplary tree might appear at a first time a, and at a later time b. Time a corresponds to the point within the utterance "the quick brown fox" immediately after the word "the" has been analyzed by the speech analysis step 10 (Fig. 1). Time b corresponds to the point at which the word "brown" has been processed. At time a the active envelope is illustrated at 74, correspond to those that are most likely to match the utterance that has been partially analyzed at this point. At later time b the active envelope has propagated outwardly, as illustrated at 76. The active node envelopes at 74 and at 76 represent the active nodes at

two different points in time (time a and time b). The algorithm operates upon these active nodes, using the currently active nodes to define the entry point into the lexical tree for the next successive iteration.

As illustrated by this example, the next active nodes evolve or propagate, much as a wavefront would propagate if a stone were dropped into a puddle of water at the root node, causing a wave to propagate outwardly with the passage of time. In a single word recognizer, the next active node wavefront would, indeed, propagate in such an outward, wavelike fashion. That is because each individual node need only be used once. In the more general case, however, such as in a continuous speech recognizer, nodes may be visited again and hence the next active node wavefront would not necessarily always propagate away from the root node. To understand why this is so, appreciate that in a continuous speech recognizer the speaker may utter a word more than once. Thus the utterance "the quick brown quick brown fox" would cause the next active node wavefront to momentarily propagate toward the root node.

Figure 5 shows the dynamic behavior of the presently preferred search algorithm. Specifically Figure 5 shows a subset of the lexical tree at different times: time = 0, time = 1... time = 4. In a frame-based recognizer these different times would correspond to successive frames. The algorithm begins at the root node at time = 0 as indicated by the active entry point arrow **100**. At time = 0 the root node is the only active

node. The algorithm then proceeds to identify the child nodes of the root node and these also become active nodes at time = 1. The algorithm uses the active envelope traversal path to visit one active node to the next. The path always begins at the deepest nodes, i.e. the ones that are
5 furthest from the root node.

At time = 1 the active node entry point is designated by the arrow labeled **100**. The active node traversal path then proceeds as indicated by arrows **102** and **104**. For purposes of illustration, example probability scores will be used, showing how the individual nodes become active and
10 are then eliminated by the beam search process. At time = 1 assume that the root node has a probability score of 100 (all scores are shown in brackets in Figure 5). Assume further that the other two active nodes have probability scores of 60 and 80, respectively. The algorithm employs
15 a beam search technique using a *beam size* defined as the maximum deviation from the best score at a given time frame. For purposes of this example, assume that the beam size is 30. The beam search algorithm specifies that a node is deleted from further processing if the probability score of that node is less than the probability score of the highest probability node by more than the beam size. In other words, if
20 probability score of a node is less than the maximum score minus 30, that node will be skipped in subsequent processing.

At time = 0 the maximum probability score is the score associated with the root node, namely a probability of 100. The beam is 100 - 30 or 70. Note that the node with a score of 60 falls below the beam and is thus subject to being cut by the beam search algorithm. Accordingly, at time

5 = 2 only two active nodes are present, the root node and the node pointed to by the active node entry arrow **100**. Because the probability scores are recomputed at each time interval, new values for each active node are computed. Assume that the root node has a probability score of 160 and the other active node a score of 120. Also note that at time = 2 the active

10 node traversal path enters at the arrow designated **100** and proceeds as indicated by the arrow **102**.

Calculating the beam at time = 2, the algorithm determines that the beam is $160 - 30 = 130$. Because the node having a probability score of 120 falls below the beam value, it is cut from further processing. Thus

15 only the root node survives the beam cut.

At time = 3 the root node remains active, and its child nodes are thereby also activated. Note that in this case, the uppermost child node that was cut by the beam search at time = 2 is reactivated at time $t = 3$ because it is a child of the active root node. Also note that the active

20 node entry point **100** identifies the deepest node and that the remaining active node arrows **102** and **104** show how the active node path is connected or defined. In the present example, assume that the root node

has a probability score of 200, the entry point node a probability score of 220 and the remaining node a probability score of 240 as illustrated at time = 3. The beam calculation $240 - 30 = 210$ now results in the root node being cut from further processing because it falls below the beam value. Thus at time = 4 the root node is no longer active. However, the child nodes associated with the lowermost node are now activated. The entry point **100** moves to the deepest node, which happens to be one of the child nodes from the previously deepest node. Arrow **102**, **104** and **106** show how the active node path would be traversed. As in the preceding cases, the entry point is always at the deepest node and the traversal proceeds such that the deepest nodes are traversed first and the traversal path ends with the parent node of the deepest node.

With the foregoing example in mind, the presently preferred algorithm will now be explained with reference to the flowchart of Figure 6 and to the detailed pseudocode listing appearing in Appendix I. With reference to Figure 6, the preferred algorithm begins at step **200** by checking to determine if the parent node of the current active node list must be removed from further consideration or "beamed out" by virtue of having a score below the beam score. Next, the active node list is traversed as indicated at **202**. The acoustic match is calculated at step **204** and the beam is updated. Next, in step **206** the algorithm performs a dynamic program match from parent to child and at step **208** the

connections are updated so that the next active node list can be traversed during time $t + 1$. The procedure then iterates with return to step **200**.

The corresponding steps from the flowchart of Figure 6 had been inserted as heading listings in the pseudocode shown in Appendix I below. Appendix II provides a pseudocode listing for the algorithm used to generate the lexical trees.

In continuous speech recognition, the processor must spend time on computation of the acoustic match, the search algorithm itself, and language modeling. Due to the late application of language model penalties, the search space must be split. Thus it may no longer be possible to store the hypotheses embedded in the lexical tree. If word-internal context-dependent models are used, however, we need only one instance of the static lexical tree. Furthermore, unigram language models (LM) can be pre-factored. They are useful for unigram or bigram language model look ahead. In addition, a vast number of nodes in the lexical tree will share the same LM look ahead score.

Appendices

Appendix I

```
20  Foreach level: active_level {  
    rho = active_level + 1  
    k_prev = scratch_node  
    ael = entry point of rho (the list at time t)  
    for(k = entry point of active_level; k != tree_end; k = k->next) {  
25  Check if the parent node has to be beamed out:  
  
    if( r_k < Beam0 ) {
```

```

    r_k = partial score = - infinity
    if( k == entry point of active level )
        entry point of active level = k->next
    /* do not increment k_prev */
5   }

```

Follow active node list:

```

    /* active node */
10  k_prev->next = k;
    k_prev = k;

```

Compute acoustic match and update the beam:

```

15  /* acoustic match */
    s_k = r_k + d_k
    /* self-activation */
    r_k = partial score = s_k + l_k
    beam = max(beam, r_k)
20  /* bequeathal */

```

Dynamic programming step from parent to child:

```

    for all children of k: c {
25  r_c = max { r_c = partial score, s_k + i_c }
    entry point of rho = min( entry point of rho, c )
    B = max{ B, r_c }

```

Keep next_active_node list connected:

```

30  switch(c) {
    ( c < ael ):
        new_ael->next = c; new_ael = c;
    ( c == ael ):
35  ael = ael->next; new_ael->next = c; new_ael = c;
    ( c > ael ):
        next = ael->next
        new_ael->next = ael
        ael = next
40  while( ael <= c ) ael = ael->next
        new_ael = c
    }
    }
    }
45  new_ael->next = ael;
    }
    Beam0 = beam - beam-width

```

Appendix II

We generate the tree with the following algorithm:

```
leftC := { {all transcriptions} }  
bin := { {null} ^ {max_state} }  
5  
do {  
  more = 0;  
  Foreach (root) in leftC {  
    split root:  
10    foreach (subtran) in root {  
      prepend transcription at bin[subtran.getNextState()]  
      if ( bin not visited )  
        insert bin into lateral list  
    }  
15    collect bins:  
    foreach bin in lateral list {  
      insert into right column unless end of word  
      more := 1  
    }  
20    serialize root into vectree  
  } while(more);  
  swap left and right columns  
}  
25
```

From the foregoing it will be seen that the present invention provides a highly compact and efficient data structure and algorithm for performing dynamic programming matching in speech recognition systems. The algorithm and data structure may be used as a replacement for the classic Viterbi algorithm in a variety of dynamic programming and recognition applications. The lexical tree structure and the active node traversal technique results in a highly memory efficient process that can be used to great advantage in recognition systems that have limited

memory and/or processing speed. The invention is therefore useful in embedded systems, consumer products and other recognition applications where large memory and fast processors may not be feasible.

5 While the invention has been described in its presently preferred embodiments, it will be understood that the invention is capable of modification without departing from the spirit of the invention as set forth in the appended claims.

10

CLAIMS

1. In a dynamic programming system, the improvement comprising:

a tree data structure implemented in a computer-readable memory
5 accessible by a processor, said tree data structure having plurality of nodes that topologically define a root node and a plurality of parent-child generations, including a deepest child generation that is topologically furthest from the root; and

a traversal algorithm implemented by said processor, said
10 algorithm traversing said nodes based on a set of traversal rules whereby nodes of a given generation are processed before the parent nodes of said given generation are processed, the deepest child generation is processed first, and traversal among nodes of each generation proceeds in the same topological direction.

2. The improvement of claim 1 wherein said tree data structure is encoded in said memory as a flat representation in which nodes of each generation occupy contiguous memory locations.

5

3. The improvement of claim 1 wherein said tree data structure is encoded in said memory with parent-child generations being represented through linked list.

10

4. The improvement of claim 1 wherein said tree data structure is encoded in said memory as a flat representation in which nodes of each generation occupy contiguous memory locations and have indicia designating the topological boundary between children of the same parent.

15

5. The improvement of claim 1 further comprising a mechanism for designating selected ones of said nodes as active nodes.

20

6. The improvement of claim 5 wherein said mechanism for designating selected ones of said nodes as active nodes comprises an active envelope data structure associated with said tree data structure.

7. The improvement of claim 1 further comprising a mechanism for designating selected ones of said nodes as active nodes and wherein said traversal algorithm includes a traversal rule whereby only active nodes are processed.

5

8. The improvement of claim 1 wherein said tree data structure is a lexical tree representing a lexicon.

9. The improvement of claim 1 wherein said tree data
10 structure is a lexical tree representing the lexicon of a speech recognizer.

10. In a dynamic programming system, the improvement comprising:

15 a tree data structure implemented in a computer-readable memory accessible by a processor, said tree data structure having plurality of nodes;

a mechanism for designating selected ones of said nodes as active nodes; and

20 a traversal algorithm implemented by said processor, said algorithm traversing said nodes based on a set of traversal rules whereby only said active nodes are traversed.

11. The improvement of claim 10 wherein said mechanism for designating selected ones of said nodes as active nodes comprises an active envelope data structure associated with said tree data structure.

5

12. The improvement of claim 10 wherein said traversal algorithm includes a dynamic programming process that assigns a likelihood score to nodes that are traversed.

10 13. The improvement of claim 12 wherein said mechanism for designating selected ones of said nodes uses said likelihood score to designate said active nodes.

14. The improvement of claim 10 wherein said traversal
15 algorithm includes a dynamic programming process that assigns a likelihood score to nodes that are traversed and wherein nodes are designated as active nodes if their likelihood score is above a predetermined threshold.

20 15. The improvement of claim 14 wherein said predetermined threshold is calculated based on the highest likelihood score.

16. The improvement of claim 10 wherein said a mechanism for designating selected ones of said nodes as active nodes defines an active envelope and uses a set of rules to propagate the active envelope by removing nodes that have a likelihood score below a predetermined
5 threshold.

17. The improvement of claim 10 wherein said a mechanism for designating selected ones of said nodes as active nodes defines an active envelope and uses a set of rules to propagate the active envelope by
10 inserting nodes that have a likelihood score above a predetermined threshold.

18. The improvement of claim 17 wherein said set of rules for inserting nodes guarantees that the nodes in said active envelope are
15 sorted by their topological index.

19. The improvement of claim 1 wherein said processor employs a cache and wherein said wherein said tree data structure is encoded in said memory such that traversal of said tree proceeds into
20 said cache.

ABSTRACT

The dynamic programming technique employs a lexical tree that is encoded in computer memory as a flat representation in which the nodes of each generation occupy contiguous memory locations. The traversal algorithm employs a set of traversal rules whereby nodes of a given generation are processed before the parent nodes of that generation. The deepest child generation is processed first and traversal among nodes of each generation proceeds in the same topological direction.




FIG 1






FIG 2




Fig 3

The Quick brown Fox

You are killed by a Hunter eats a big bird






FIG 4a




START
HERE

FIG 4b


time = 0




time = 1



time = 2



time = 3



time = 4





FIG 5

FIG 6



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Recognition System Using Lexical Trees

the specification of which (check one)

☒ [X] is attached hereto.

☐ [] was filed on _____ as Application
Serial No. _____ and was amended on
_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application or to the patentability of the invention claimed therein in accordance with Title 37, Code of Federal Regulations, section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, section 119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

Priority Claim

_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)	_____ Yes	_____ No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)	_____ Yes	_____ No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)	_____ Yes	_____ No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States Provisional application(s) listed below:

PRIOR PROVISIONAL APPLICATIONS

(application serial number)

(Month / Day / Year filed)

(application serial number)

(Month / Day / Year filed)

I hereby claim the benefit under Title 35, United States Code, section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.

Filing Date

**Status - patented,
pending, abandoned**

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint Gregory A. Stobbs, Reg. No. 28,764, and each principal, attorney of counsel, associate and employee of Harness, Dickey & Pierce, P.L.C., who is a registered Patent Attorney, my attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. I request the Patent and Trademark Office to direct all correspondence and telephone calls relative to this application to Harness, Dickey & Pierce, P.L.C., P. O. Box 828, Bloomfield Hills, Michigan 48303 (248) 641-1600.

Full name of sole or first inventor: Luca Rigazio

Inventor's signature: Luca Rigazio

Date: 7-28-2000

Residence: 165 San Angelo Avenue, Apt # G, Santa Barbara, CA 93111

Citizenship: Italy

Post Office Address: SAME

Full name of second joint inventor, Patrick Nguyen _____

Second Inventor's signature: Patrick Nguyen

Date: 7/28/00

Residence: 1117 E. Cota Street, #A, Santa Barbara, CA 93103 _____

Citizenship: Switzerland _____

Post Office Address: SAME

Full name of third joint inventor, if any: _____

Third Inventor's signature: _____

Date: _____

Residence: _____

Citizenship: _____

Post Office Address: _____

Full name of fourth joint inventor, if any: _____

Fourth Inventor's signature: _____

Date: _____

Residence: _____

Citizenship: _____

Post Office Address: _____

Full name of fifth joint inventor, if any: _____

Fifth Inventor's signature: _____

Date: _____

Residence: _____

Citizenship: _____

Post Office Address: _____